



PERFORMANCE CURVE

Models:
S4T
V4T
V4TR

6-Blade Impeller
4" Discharge

| CURVE | POWER (HP/KW) | SPEED (RPM) | IMPELLER DIAMETER |
|-------|---------------|-------------|-------------------|
| A | 40 / 30 | 1460 | 11.80" (300mm) |
| B | 30 / 22 | 1460 | 11.30" (287mm) |
| C | 25 / 19 | 1460 | 11.00" (279mm) |
| D | 25 / 19 | 1460 | 10.80" (274mm) |
| E | 20 / 15 | 1460 | 10.30" (262mm) |
| F | 20 / 15 | 1460 | 9.90" (241mm) |
| G | 15 / 11 | 1460 | 9.50" (241mm) |
| H | 15 / 11 | 1460 | 8.90" (226mm) |

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A. CAPACITY (U.S. GALLONS PER MINUTE)

